

Product Information

Self adhesive PET-film with a Silicon adhesive. The adhesive has an excellent resistance to chemicals and high temperature.

The polyester carrier has high tensile and tear strength.

Especially to be emphasised are the following properties:

- Good initial tack level.
- Specially developed to stick to silicone treated surfaces, for example to splice silicone papers and due to the formulated adhesive it is resistant to very high temperatures.

Technical Data

Carrier:	PET-film, green translucent	
Adhesive:	Silicone-Rubber	
Adhesion [N/cm]:	3,60	+/- 10 %
Thickness [mm]:	0,06	+/- 5 %
Temperature resistance [°C]:	-40 / +120	

Standard Dimensions

900 mm x 66 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.