

## Product Information

Double-sided mounting tape based on a durable elastic, compressible foam carrier based on ethylvinylacetate.

POLI-MOUNT 3605 offers a high initial tack even on rough and critical substrate surfaces such as polyethylene or polypropylene. The adhesive has a high resistance against ageing, UV and weathering.

Especially to be emphasised are the following properties:

- Mounting of injection moulded and extruded plastic objects such as PVC cable trunkings, cover plates, hooks and holders.
- Mounting of displays, product samples, plates and screens.
- Self-adhesive mounting of unpolar plastics such as polyethylene, polypropylene and polystyrene.

## Technical Data

<b>Carrier:</b>	EVA-foam
<b>Adhesive:</b>	Solvent acrylic
<b>Liner:</b>	Silicone-paper, white (120 g/m <sup>2</sup> )
<b>Adhesion [N/cm]:</b>	4,70      +/- 10 %
<b>Thickness [mm]:</b>	1,00      +/- 5 %
<b>Temperature resistance [°C]:</b>	-20 / +70

## Standard Dimensions

1.010 mm x 50 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.