

Product Information

Double-sided mounting tape based on an UV-cross-linked polyethylene foam coated with a modified acrylic adhesive with high adhesion on both sides. POLI-MOUNT 370 offers a high resistance against ageing, UV and weathering.

The durable elastic foam carrier guarantees a high initial tack on structured and rough surfaces like concrete and structural varnish. Composite materials with extremely different expansion rates can be mounted without tension.

POLI-MOUNT 370 is suitable for the mounting of spotlights, cover plates, plates, cable trunkings, displays, hooks and wall mounts based on different materials like PVC, ABS, polystyrene, wood, glass and ceramic.

Technical Data

| | | |
|-------------------------------------|--|----------|
| Carrier: | PE-foam | |
| Adhesive: | Acrylic, modified | |
| Liner: | Silicone-paper, white (90 g/m ²) | |
| Adhesion [N/cm]: | 3,60 | +/- 10 % |
| Thickness [mm]: | 1,00 | +/- 5 % |
| Temperature resistance [°C]: | -20 / +70 | |

Standard Dimensions

1.500 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.