

## Product Information

Flexible PET-film with a high tack Silicon adhesive. The adhesive has an excellent resistance to chemicals, ageing, humidity and high temperature.

Suitable for positioning of Flock- and Flex-products before and during thermal transfer.

## Technical Data

<b>Carrier:</b>	PET-film, green	
<b>Adhesive:</b>	Silicon-Rubber	
<b>Adhesion [N/cm]:</b>	3,60	+/- 10 %
<b>Thickness [mm]:</b>	0,06	+/- 5 %
<b>Temperature-resistance [°C]:</b>	max. 200	

## Standard Dimensions

9 mm x 66 m  
12 mm x 66 m  
19 mm x 66 m  
25 mm x 66 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.