

Product Information

Transparent Application Tape made of an embossed cast Polypropylene film. PT 95 can be torn by hand in both directions. The product offers dimensional stability and excellent lay-flat properties.

Due to the high tack acrylic adhesive, computer cut letters, images and logos, made of cast or calendered CAD/CAM plotter films can easily be transferred.

Especially to be emphasised are the following properties:

- The excellent lay-flat property guarantees excellent lamination without wrinkles, even on large motifs.
- To guarantee an easy processing, the film can be torn by hand in both directions.
- Easy unwinding of the film with low static charge.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Suitable for dry and wet applications.

Technical Data

Carrier:	Polypropylene film, pyramid surface	
Adhesive:	Acrylic, modified	
Adhesion [N/cm]:	1,70	+/- 10 %
Thickness [mm]:	0,14	+/- 5 %

Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.