

## Product Information

Application Tape based on a special impregnated paper with low tensile elongation and high wet strength.

Suitable for transferring self adhesive letters produced from cast and calendered PVC coloured films according to CAD/CAM techniques.

Especially to be emphasised are the following properties:

- The Ageing- and UV-stabilised natural rubber adhesive guarantees an excellent adhesion on PVC films because of the relatively high coating weight.
- The impregnated carrier paper shows an excellent stability of shape, with no curling even under moist conditions.
- Due to the release coating on the carrier paper, the whole roll unwinds easily.

## Technical Data

<b>Carrier:</b>	Special paper with release
<b>Adhesive:</b>	Natural rubber
<b>Adhesion [N/cm]:</b>	3,00      +/- 10 %
<b>Thickness [mm]:</b>	0,11      +/- 5 %

## Standard Dimensions

1.220 mm x 100 m
1.220 mm x 91,4 m
1.000 mm x 100 m
1.000 mm x 91,4 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.