

## Product Information

Application Tape based on an impregnated special paper coated with a high tack natural rubber adhesive. Allows corrective repositioning after transfer.

Suitable for transferring die-cut or computer cut lettering and symbols of all types of self adhesive vinyls.

Especially to be emphasised are the following properties:

- Due to a high conformity (adherence) to nonpolar surfaces, it offers excellent adhesion to silicone papers. This prevents unwanted delaminating of the film from the liner.
- Especially suitable for wet application. The product is smoothly removable without residue.
- POLI-TAPE 140 is cuttable to required widths by single-blade cutting. The cut is clean with no adhesive residue on the edges. No more paper tearing during unwinding.
- Perfect tear. POLI-TAPE 140 can be cleanly torn leaving no adhesive strings.

## Technical Data

<b>Carrier:</b>	Special paper, impregnated
<b>Adhesive:</b>	Natural rubber
<b>Adhesion [N/cm]:</b>	2,20      +/- 10 %
<b>Thickness [mm]:</b>	0,12      +/- 5 %

## Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.