



# POLI-WALL Interior decoration 7700 DELUXE BRILLANT

## Product Information

Soft and smooth wall decoration film (white glossy, 100  $\mu$ ) for short-term interior wall application.

The ultrasmooth adhesive technology allows an excellent adhesion to different kinds of wall surfaces like woodchip wallpaper, stucco, textured wallpaper, wood-, glass- and varnish surfaces.

Easy peel-off without any residues. POLI-WALL DELUXE films fit perfectly to the substrate structure.

Digital printable with Solvent-, Eco-, Mild-, Low-Solvent, Latex- and UV-inks.

## Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

## Standard Dimensions

1050 mm x 50 m

1370 mm x 50 m

## Technical Data

<b>Carrier:</b>	monomeric PVC, highly stabilized, calendared
<b>Thickness:</b>	100 $\mu$ +/- 5 %
<b>Adhesive:</b>	clear acrylic dispersion, removable
<b>Adhesion:</b>	2,2 N/cm +/- 5%
<b>Liner:</b>	one-sided clay-coated silicone paper (135 g/m <sup>2</sup> )
<b>Tensile strength md:</b>	>8,8 kN/m
<b>Tensile strength cd:</b>	>5,0 kN/m
<b>Application temperature:</b>	+10 - +40 °C
<b>Service temperature:</b>	- 20 - +50 °C
<b>Outdoor durability:</b>	3-5 years (unprinted film)
	<b>Maximum 6 months residue-free removable.</b>

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0  
Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.