



POLI-WALL Interior decoration 7800 VELVET PRINT

Product Information

Individually printable pressure sensitive velvety textile with strong adhesive (white matt).

It is developed for unlimited and creative interior decorations of:

- ornaments and little motifs on glass
- lampshades
- mirrors
- pillows
- candles
- bags
- laptops
- mobile phones, etc.

As wall tattoo or in combination with POLI-WALL 7600 and 7700 series the fluffy and velvety surface gives a comfortable ambience.

Digital printable with Solvent-, Eco-, Mild-, Low-Solvent, Latex- and UV-inks.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Technical Data

Carrier:	Special textile
Adhesive:	Acrylic adhesive
Adhesion:	0,5 N/cm +/- 5%
Liner:	Silicone-Paper, white

Standard Dimensions

500 mm x 25 m

1.000 mm x 25 m

500 mm x 10 m

1.000 mm x 10 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.